



SDS for GHS: Hazcom 2012 (USA) / WHMIS 2015 (Canada) / NMX-R-019-SCFI-2011 (Mexico)

SECTION: 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND COMPANY

- 1.1 Product Name: Coolant Fluid
Product Identification:
- Product Specification:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:
- 1.2.1 Relevant identified uses: For welding consumables and related products.
- 1.2.2 Uses advised: Reference the [7. Handling and storage]
- 1.3 Details of the supplier of the safety data sheet:
Supplier: Elderfield & Hall, Inc.10901
McBride LaneKnoxville TN
37932
Emergency telephone number: 865-671-7682
Email: sales@pro-fusiononline.com
Website: www.pro-fusiononline.com
Revision: 22 March 2016

SECTION: 2 HAZARDS IDENTIFICATION

- 2.1 Classification of the mixture:
The product is placed on the market in solid form
- 2.1.1 Classification in accordance with GHS-US
- | | |
|----------------|------|
| Acute Toxicity | H302 |
| Eye irritation | H320 |

- 2.2 Label elements:
GHS-US labeling

Hazard Pictograms (GHS-US):



Signal word (GHS-US):

Danger

Hazard statements (GHS-US):

- | | |
|-------------|---|
| <u>H302</u> | Harmful if swallowed |
| <u>H320</u> | Causes eye irritation |
| <u>H373</u> | May cause damage to organs (kidney) through prolonged or repeated exposure if swallowed |

Precautionary statements:

- | | |
|------------------------|---|
| <u>P260</u> | Do not breathe dust/fume/gas/mist/vapours/spray |
| <u>P264</u> | Wash skin thoroughly after handling |
| <u>P270</u> | Do not eat, drink or smoke when using this product. |
| <u>P301+ P312+P330</u> | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. |
| <u>P314</u> | Get medical advice/attention if you feel unwell. |
| <u>P501</u> | Dispose of contents and container in accordance with local regional/national international regulations. |

- 2.3 Other hazards: No additional information available
- 2.4 Unknown acute toxicity (GHS-US): No data available.

Coolant Fluid

SAFETY DATA SHEET



SECTION: 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances: No data available

Full Text of H-phrases: see section 16

3.2 Mixtures: The mixture contains dangerous substances:

Substance name		Product Identifier (CAS No)	% Percent	GHS-US classification
Ethylene glycol	C ₂ H ₆ O ₂	107-21-1	10 - <25	Acute Tox 4, H302

SECTION: 4 FIRST AID MEASURE

4.1 Description of first aid measures:

First-aid measures after inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and get medical attention.

First-aid measures after skin contact: Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.

First-aid measures after eye contact: Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.

First-aid measures after ingestion: Do NOT induce vomiting. Get immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed:

Symptoms/injuries after inhalation: Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with Flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.

Symptoms/injuries after skin contact:

Dusts may cause irritation.

Symptoms/injuries after eye contact:

Causes eye irritation.

Symptoms/injuries after ingestion: Not an anticipated route of exposure during normal product handling. May be harmful if ingested.

4.3 Indication of any immediate medical attention and special treatment needed: No data available.

SECTION: 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media: No data available.

5.2 Special hazards arising from the substance or mixture: Fire may produce irritating or poisonous gases.

Fire hazard:

Not flammable

Explosion hazard:

None known

5.3 Advice for firefighters: In the event of fire, wear self-contained breathing apparatus and full protective gear.

Coolant Fluid

SAFETY DATA SHEET



SECTION: 6 ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:
For non-emergency personnel: Wear appropriate personal protective equipment as specified in Section 8. Ensure adequate ventilation.
For emergency responders: No data available.
- 6.2 Environmental precautions: Avoid release into the environment. Avoid dispersal of spilled material and contact with soil, ground and surface water drains and sewers.
- 6.3 Methods and material for containment and cleaning up: Take up mechanically. Collect the material in labeled containers and dispose of according to local and regional authority requirements.
- 6.4 Reference to other sections: See Section 7 for information of safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION: 7 HANDLING AND STORAGE

- 7.1 Precautions and safe handling: Welding may produce dust, fumes and gases hazardous to health. Avoid breathing dust, fumes and gases. Use adequate ventilation. Keep away from sources of ignition. Avoid contact with skin, eyes and clothing. Do not eat, drink and smoke in work areas.
- 7.2 Conditions for safe storage, including and incompatibilities: Store in cool, dry and well-ventilated place. Keep away from incompatible materials. Keep away from heat and open flame.
- 7.3 Specific end use(s): For welding consumables and related products.

SECTION: 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 Control parameters: Exposure limits were not established for this product

Ethylene glycol (CAS No) 107-21-1		
USA ACGIH	ACGIH (TWA) (mg/m ³)	100 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	100 mg/m ³

8.2 Exposure controls:

Appropriate engineering controls: local exhaust and general ventilation must be adequate to meet exposure standards.

Hand protection: Wear welding gloves.

Eye protection: Wear helmet or face shield with filter lens of appropriate shade number. See ANSI/ASC Z49.1 Section 4.2. Provide protective screens and flash goggles, if necessary, to shield others.

Skin and body protection: Wear head and body protection, which help to prevent injury from radiation, sparks, flame and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the employee not to touch live electrical parts and to insulate him/herself from work and ground. Welders should not wear short sleeve shirts or short pants.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Coolant Fluid

SAFETY DATA SHEET



SECTION: 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Physical state:	- liquid
Appearances:	- Clear Colorless liquid
Color:	- Clear
Odor:	- Odorless
Odor threshold:	- Not determined
pH:	- 6
Relative evaporation rate (butyl acetate = 1):	- No data available
Melting point:	- (-7°C)
Freezing point:	- No data available
Initial boiling point and boiling range:	- (93°C)
Flash point:	- No data available
Self ignition temperature:	- Product is not self igniting
Decomposition temperature:	- No data available
Flammability (solid, gas):	- No data available
Vapour pressure:	- 24(MMHG)
Relative vapour density at 20° C:	- 1.025 (Air = 1)
Relative density:	- No data available
Solubility(ies)	- Fully miscible
Log Pow:	- No data available
Log Kow:	- No data available
Viscosity, kinematic:	- No data available
Viscosity, dynamic:	- No data available
Explosive properties:	- No data available
Oxidizing properties:	- No data available
Explosive limits:	- No data available

9.2 Other information: No additional information available.

SECTION: 10 STABILITY AND REACTIVITY

10.1 Reactivity: No additional information available.

10.2 Chemical stability: The product is stable under normal conditions. When using it may produce dangerous fumes and gases.

10.3 Possibility of hazardous reactions: Will not occur.

10.4 Conditions to avoid: None

10.5 Incompatible materials: None

10.6 Hazardous decomposition products: Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and welding consumables used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coating on the metal being welded (i.e. paint, painting, galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from the cleaning and degreasing activities).

When an electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 3, plus those from the base metal coating, etc., as noted above. Reasonable expected fume constituents of this product would include: Complex oxides of iron, manganese, silicon, chromium, nickel, columbium, molybdenum, copper, carbon dioxide, carbon monoxide, ozone and nitrogen Oxides. Some products will also contain antimony, barium, molybdenum, aluminum, columbium, magnesium, strontium, tungsten, and or zirconium. Fume limit for chromium, nickel and or manganese may be reached before limit of 5 mg/m³ of general welding fumes is reached.

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.3 and F1.5, available from the American Welding Society.

Coolant Fluid

SAFETY DATA SHEET



SECTION: 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Acute toxicity: Harmful if swallowed

Substance name	CAS number	LD50 oral rat (mg/kg)	ATE (oral) (mg/kg)	Comments
Ethylene glycol	107-21-1	4700 mg/kg	10,626 mg/kg	
Skin corrosion/irritation:		May cause skin irritation		
Serious eye damage/irritation:		May cause eye irritation		
Respiratory or skin sensitization:		May cause an allergic skin reaction.		
Germ cell mutagenicity:		May cause damage to organs		
Carcinogenicity:		Not classified		
Reproductive toxicity		Not classified		
Specific target organ toxicity (single exposure):		Not classified		
Specific target organ toxicity (repeated exposure):		Causes damage to organs through prolonged or repeated exposure		

SECTION: 12 ECOLOGICAL INFORMATION

12.1 Toxicity:

Ecology - general: No data available.

Ethylene glycol	(CAS No) 107-21-1
LC50 fishes 1	18,500 mg/l (Exposure time: 96 h - species: Oncorhynchus mykiss)
EC50 Daphnia 1	74,000 mg/l (Exposure time: 24 h - species: Daphnia magna [static])
EC50 other aquatic organisms 1	10,000 mg/l (Exposure time: 96 h - species: Leuciscus idus [static])
LC50 fish 2	32,000 mg/l (Exposure time: 96 h - species: Pimephales promelas ([semi-static])

12.2 Persistence and degradability: No additional information available.

12.3 Bioaccumulative potential: No additional information available.

12.4 Mobility in soil: No additional information available.

12.5 Other adverse effects: No additional information available.

SECTION: 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods: Dispose of in accordance with local and national regulations.

Waste disposal recommendations: Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION: 14 TRANSPORT INFORMATION

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN Number: Not a dangerous good in sense of transport regulations

14.2 UN proper shipping name: Not applicable

SECTION: 15 REGULATORY INFORMATION

15.1 US Federal Regulations:

Coolant Fluid

SAFETY DATA SHEET



Ethylene glycol	(CAS No) 107-21-1
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting 1.0% (dust or fume only)	

15.2 US State Regulations:

Ethylene glycol (CAS No) 107-21-1				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes	Yes	Yes	Yes	

Ethylene glycol	(CAS No) 107-21-1
U.S. - Massachusetts - Right To Know List	
U.S. - Minnesota - Hazardous Substance List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Coolant Fluid

SAFETY DATA SHEET



SECTION: 16 OTHER INFORMATION

- Full text of H-phrases:

Carc. 1A	Carcinogenicity, Category 1A
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure.



- NFPA health hazard: 2 – Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA fire hazard: 0 – Materials that will not burn.
- MFPA reactivity: 0 – Normally stable, even under fire exposure conditions, and are not reactive with water
-
- HMIS III Rating
- Health: 2 - Moderate Hazard
- Flammability: 0 - Minimal Hazard
- Physical: 1 - Moderate Hazard

DISCLAIMER: *The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of its publication.*

The information is provided as guidance and is not considered a warranty or quality specification. It is the user's obligation to determine the conditions of safe use of these products.

EMERGENCY CONTACT: ELDERFIELD & HALL (800) 747-9353

Prepared by: R. Hall